

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number
WO 03/073955 A1(51) International Patent Classification:
A61B 17/66

A61C 7/00,

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/IB03/00822


(22) International Filing Date: 6 March 2003 (06.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0205299.1 6 March 2002 (06.03.2002) GB
0301348.9 21 January 2003 (21.01.2003) GB

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and
(72) Inventor: DAWOOD, Andrew, J., S. [GB/GB]; 45, Wim-
pole Street, London, W1M 8SB (GB).Published:
— with international search report(74) Agent: OLSSON, Gunnar; Nobel Biocare AB (publ),
Box 5190, S-402 26 Goteborg (SE).For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: A FIXTURE FOR ORTHODONTIC ANCHORAGE AND OSSEO-DISTRACTION OF THE ALVEOLAR PROCESS,
AND FOR THE STABILIZATION OF TEMPORARY PROSTHESES(57) Abstract: The invention relates to a fixture for orthodontic and osseo distrac-
tion of the alveolar process, and for the stabilization of temporary prostheses. The
fixture has an external threading, comprising a threaded part for insertion into a
prepared site in the jawbone, and a threaded part, to which pressure may be applied by
means of an internally threaded element e.g. a nut, when used in conjunction with
an appliance supported by teeth or adjacent static fixtures.

WO 03/073955 A1

Best Available Copy

WO 03/073955

3 / PRTS

DT17 c'd PCT/PTO 07 SEP 2004
PCT/IB03/00822

10/506632

A Fixture for Orthodontic Anchorage and Osseo distraction of the Alveolar Process, and for the Stabilization of temporary prostheses.

Dental implants are fixtures, which are commonly inserted into the jawbones in order to support dental prostheses. The fixture described herein is intended as a multipurpose anchor, which may be used to facilitate bone movement in the Osseo distraction process, as a temporary anchorage unit for Orthodontic movement of teeth, and as an anchor for dental prostheses.

Osseo Distraction

For, many reasons, there are often situations in which there is inadequate bone available in which to place fixtures. In these situations, various techniques exist which may be used to augment the available bone bulk.

Osseo-distraction (distraction Osseo-genesis) is a surgical process by which the ~~available bone bulk may be increased.~~ This process may be used where there is a local deficiency in jawbone height, prior to the provision of implant-stabilised prostheses. Surgery involves sectioning a segment of the jaw, which must be pedicled on the surrounding soft tissue.

Subsequently, soft tissues are allowed to heal and the bone callus to develop. However after a few days latency, the bony "transport" segment is distracted, thus stretching the healing callus. Distraction proceeds incrementally, and substantial volumes of new bone may be laid down between the transport segment and the bony jaw base.

Varied fixtures and mechanisms have been developed to facilitate this process.

WO 03/073955

PCT/TB03/00822

Orthodontic tooth movement

When teeth are poorly positioned from either a cosmetic or a functional point of view, their position may be changed by the application of forces via springs or other appliances. Newtons Third Law means that a force applied to a tooth will be countered by an equal and opposite force applied to the tooth or teeth to which the spring is anchored. This limits the rate at which teeth may be moved and may complicate orthodontic treatment.

Dental implants, which are osseointegrated, form a firm, stable connection to the bone, which may not be changed by the application of orthodontic forces. This means that a dental implant may form an ideal anchor for orthodontic movement of teeth.

Provisional Anchorage of Temporary Dental Prostheses

There are many situations where it is desirable to be able to provisionally replace teeth, e.g. whilst healing takes place in future implant sites, or during the orthodontic alignment of teeth adjacent to a future implant site

A provisional implant should be easily placed, easily removed, and should provide means for the ready fixation of teeth.

This invention relates to a fixture type and related components, intended to facilitate the distraction process, act as a stable anchorage unit for the connection of an orthodontic appliance, and which may also act as a provisional support for temporary restorations

A specific embodiment will now be described: With reference to Figure 1, there is provided a fixture, which may be made of machined titanium or a titanium alloy. The fixture may broadly be categorized as containing three segments.

An alignment section (1) is provided having a smooth surface, and as in this case a relatively small diameter. A bone interfacing (2) retentive section is provided having a deep-set steeply pitched thread on a slightly tapered base (taper exaggerated in diagram). In some situations, the surface of this section of the fixture may be roughened, or coated, e.g. with hydroxyapatite, to encourage rapid osseointegration.

A non-axially symmetrical collar (3) facilitates insertion of the device by means of a matched insertion tool, which fits over the intra oral part (4) of the fixture, rather like a socket spanner. This part is polished to allow a gingival cuff to develop around the fixture.

WO 03/073955

PCT/IB03/00822

The intra oral part of the fixture (4) comprises a narrow extension provided with a machine screw threading, but having a single flattened side (5).

Surgery proceeds as follows, with reference to figures 1 & 2:

Following elevation of a surgical flap, a horizontal osteotomy is performed (A) at the base of the future transport segment (B).

Before the transport section is mobilized by the vertical osteotomies (C), a site is prepared for the distraction fixture or fixtures; having marked the site with a round burr a 1.2mm twist drill is inserted beyond the depth of the horizontal osteotomy, such that the site is prepared in bone of good bulk and quality.

A second twist drill is then inserted into the prepared site, having a slightly greater diameter, e.g. 1.6mm, to the depth of the horizontal osteotomy

If visibility and access to the site is unimpaired the surgeon may then continue to carry out the vertical osteotomy, thus freeing the transport section. However generally the osteotomy is only carried out to an extent, which will allow the transport segment to be easily mobilized once the fixtures have been placed.

The distraction fixture is then placed by means of an insertion tool that properly mates with the non-axially symmetrical collar such that the alignment section (1) travels through the narrowly prepared depth of the site (D). The threaded section (2) is tapped through the prepared site such that it engages the transport segment.

The threaded intra oral section (4) then protrudes into the mouth such that it is aligned with adjacent teeth or fixtures, and the main bulk of the bone is in the intended trajectory.

Following latency, typically a healing period of four-seven days, distraction may begin. For distraction to take place there may be provided either a temporary prosthesis which serves to provisionally replace the missing teeth, or a simple appliance, (E), which may take the form of a cast bar, resin reinforced structure, or orthodontic appliance anchored to adjacent teeth of fixtures.

A prosthesis or appliance may be provided with a portion through which the threaded part of the distraction implant protrudes. Distraction may then be accomplished by tightening a nut (6) onto the machined threaded section so as to pull it through the channel, thus distracting the bony segments. As the portion of the threaded section protrudes past the nut, it may be sectioned so as to avoid interference within the mouth. Once distraction has taken place to the planned extent the arrangement is left in place for a subsequent period of six-eight weeks until the transport segment has stabilised, and bone has formed in the space between the segment and the bony base.

An orthodontic appliance may be fitted with a matched component, (e.g as illustrated in figures 6 and 7 (cross section)), which is designed to fit onto the arch wire of a

WO 03/073955

PCT/IB03/00822

fixed appliance, and mate with the head of the distraction fixture, thus allowing the distraction process to be controlled accurately in three dimensions.

Where large distraction movements must take place, there may also be provided similar fittings having extension pieces having an internal thread, which may be rotated over the threaded head of the fixture, to extend the reach of the component.

A further embodiment will now be presented in which connection to a prosthesis or Orthodontic appliance constrains movement, allowing for simplification of the fixture, which may act as an anchor for Orthodontic procedures or Osseo distraction:

Fixed Orthodontic appliances with e.g. Square arch wires provide excellent control over tooth movements in all dimensions. Such appliances used in conjunction with an anchor placed in the transport segment will equally permit multi dimensional control of the distraction process, without necessitating penetration of the fixture beyond the horizontal osteotomy.

Figure 3 illustrates a fixture having a bone interfacing retentive section (2) provided with a deep-set steeply pitched thread on a slightly tapered base.

A non-axially symmetrical collar (3) facilitates insertion of the device by means of a matched insertion tool, which fits over the intra oral part (4) of the fixture, rather like a socket spanner. This part is polished to allow a gingival cuff to develop around the fixture.

The intra oral part of the fixture (4) comprises a narrow extension provided with a machine-screw threading, but having a single flattened side (5).

Towards the middle of the intra oral part of the fixture there is provided a square or rectangular aperture (6).

A cylindrical Orthodontic fitting (Figure 5) is provide having a matched internally threaded section which may be rotated over the threaded intra oral part of the fixture, to a varying degree by means of a spanner. At least one aspect of this fitting has a surface conducive to dental bonding materials, which will permit bonding of an orthodontic bracket.

Alternatively, a similar fitting may be provided, without internal threading, intended for direct cementation, additional stability being provided by the flattened side (figure 8).

For distraction purposes, a variation on the orthodontic fitting described above may be provided (figures 6 and 7), having a freely rotating bush (9) around its body (8), to which an orthodontic bracket may be attached.

WO 03/073955

PCT/IB03/00822

Construction of Laboratory-made prostheses or appliances may also be facilitated by provision of impression copings of matched dimensions, which fit over the threaded portion of the fixture, engaging the flattened side.

For the retention of crown and bridge work:

In addition to the Orthodontic and Distraction utility of the fixture, there is also the option to use such a fixture to retain crown or bridge work, for which purpose there may be provided prefabricated copings in metal alloy, or in plastic for use e.g. as a burn out or impression coping, or which may either be cemented directly over the threaded intra oral part, mating with the flattened side so as to locate accurately into position and to resist rotational forces, or alternatively be cemented or clipped into place over the Orthodontic fitting; it may in some cases be expedient to incorporate an orthodontic bracket into a temporary restoration. So as to achieve the best possible appearance for provisional restorations the prefabricated copings may engage the wider collar.

For Orthodontic or distraction movements, the fixture and the various fittings may be simply used in conjunction with a fixed orthodontic appliance. Figure (4) illustrates possible usage of the orthodontic anchor to anchor an orthodontic arch wire.

The fixtures may be placed in the same axis as the teeth or may be used horizontally, in which case the square aperture (figure 3, (6)) will provide useful connectivity to an appliance.

Connection of the Orthodontic or distraction fitting to the intra oral part of the fixture permits the fixture to be linked to an appliance, either to provide anchorage for orthodontic movements or to stabilize the transport segment of bone during distraction.

Movement of teeth or Osseo distraction may be achieved in every dimension by varying the position of the fitting on the fixture, changing the relative position of the orthodontic brackets, or by changes in the shape of the orthodontic arch wire.

Surface considerations for the provisional fixture

Although a fixture having a conventional milled surface may achieve good initial stability in a well-prepared site in bone of reasonable quality, the stability of the fixture may be less than ideal in soft bone, or in a poorly prepared site, and may suffer further if the fixture is rapidly subjected to heavy loading, before osseointegration has had time to develop.

Dental implants have been developed with various types of "rough" surfaces, which will increase the rate of bony integration of the fixture. It has been shown that

WO 03/073955

PCT/IB03/00822

titanium or titanium alloy fixtures having such surface treatments, e.g. plasma spraying, sand blasting, acid etching, hydroxy apatite coatings or titanium dioxide coatings will integrate more rapidly, so that the fixture may be more rapidly loaded.

It has also been established that fixtures having rough surfaces which may be exposed to the oral cavity, may become affected by and be prone to inflammation of the gingival cuff (perimplantitis), as a result of rapid and persistent bacterial colonisation of the roughened surface.

In an attempt to circumvent these problems fixtures have been designed such that the surface of that part of the fixture intended to be submerged beneath bone is treated to encourage bony anchorage, whilst that part of the fixture which approximates, or may eventually approximate the gingival tissues has a smoother surface. Fixtures have been described having both incrementally, progressively, rougher surfaces towards the apex of the fixture and a smoother surface towards the gingival aspect, and also having a roughened apical portion, with a machined gingival portion, such that the most superficial screw threads have a machined surface.

When considering the temporary fixture, it is evident that early integration is extremely desirable, and that longer term bacterial colonisation less of a worry for a fixture that is intended to be used only in the short term.

However a temporary fixture with an overall surface treatment would be relatively difficult to remove if fully osseointegrated, as fixtures having rough surface treatments are extremely difficult to rotate out of the bone.

This invention relates to a fixture for temporary or provisional use, in which the apical part of the fixture has a machined, or otherwise relatively smooth surface, whilst the coronal part of the bone approximating thread has a rough surface treatment so as to encourage rapid bony integration of the fixture, particularly where the coronal threads pass through the cortex of the bony site.

Alternatively the fixture may have a surface that is progressively rougher when proceeding from apex to the gingival approximating portion.

In use the fixture may be inserted into a freshly prepared site. If initial stability is high the fixture may be rapidly loaded, and as osseointegration proceeds the stability will increase. Whilst initial stability is largely a function of the implant shape and the anatomy of the bony site, secondary stability will be greatly enhanced as a result of osseointegration, which will proceed most rapidly adjacent to the bony cortex and the treated implant surface. This is clearly all the more important when initial stability is low.

Implant Removal: Having used the implant for its intended purpose, it will then be necessary to undertake removal, which may in some cases be achieved by simple counter rotation of the fixture to break the bony union.

This may however result in fracture of the fixture at or around the level of the bony crest.

WO 03/073955

PCT/IB03/00822

In this case, a trephine may be used to cut around the fixture. The fact that the "rough" surface treated portion of the fixture does not extend along the full length of the endosseous part of the fixture means that, removal is facilitated, as there is a reduced need to use the trephine to the full depth of the fixture, thus preserving bone in the area. Indeed removal may be accomplished by means of a matched trephine.

WO 03/073955

PCT/IB03/00822

Claims

1. A fixture having external threading, comprising, 1/ a threaded Part for insertion into a prepared site in the jaw bone, and 2/ a threaded part, to which pressure may be applied by means of an internally threaded element e.g. a nut, when used in conjunction with an appliance supported by teeth or adjacent static fixtures.
2. A one piece implant for osseodistraction or orthodontic anchorage, having a threaded part for insertion into bone, with the characteristics of a dental implant for insertion into bone, at one end, and the characteristics of a machine screw at the other end, which is intended to protrude into the mouth, for the connection to appliances, or prostheses, for the distraction of bone or the orthodontic movement of teeth.
3. A fixture as described in previous claims, having two externally threaded parts, one which is inserted into a prepared site into the jaw bone, the other which protrudes into the oral cavity so that it may be acted upon by an internally threaded components.
4. A fixture as described in previous claims having an externally threaded part which protrudes into the oral cavity, said part having a flattened aspect, such that it may be acted upon either by an internally threaded component, or by cement on female components, or clip on female components, which mate with said flattened aspect to prevent rotation of the component.
5. A fixture as described in the previous claims having a smooth, non threaded, alignment section at its' apex, intended to guide the transport segment of bone as it is distracted and prevent inappropriate movement.
6. A fixture as described in previous claims, which is provided with a polished section, intended to act as a collar to which the gingival cuff will approximate, said collar having a non round cross-section to allow insertion of the fixture with an appropriate shaped socketed tool.
7. A fixture as described in previous claims intended for connection to prostheses, orthodontic appliances, or adjacent teeth or dental implants.

WO 03/073955

PCT/IB03/00822

8. A fixture as described in previous claims intended for connection to orthodontic appliances, having within its body an aperture, which may be square or rectangular through which an orthodontic wire may be passed to facilitate connection of said fixture to adjacent teeth or appliances..
9. A fixture as described in previous claims having a slightly tapered body, having deeply biting threads, on that part intended for insertion into the jaw, and a metric machine thread on that part intended to protrude through the gingiva.
10. A fixture intended for Osseo distraction or Orthodontic anchorage, substantially as described in this description and the accompanying figures.
11. A fixture range or system intended for orthodontic anchorage in the jaw, substantially as described in this description and the accompanying figures,
12. A fixture range or system intended for Osseo distraction, or for orthodontic anchorage in the jaw, having available matched components, provided with fittings to facilitate the connection of arch wires, or the cementation of orthodontic components substantially as described in this description and the accompanying figures.
13. A fixture as described in previous claims having a surface treatment intended to encourage rapid osseointegration, e.g. plasma sprayed, etched, blasted, titanium dioxide, hydroxy-apatite or other roughening processes, on only the more superficial endosseous part of the fixture which is intended to contact the bony cortex of the intended site, and a smoother, possibly machined surface towards the apical portion of the fixture.
14. A fixture as described in previous claims having a progressively rougher surface, which is relatively smooth toward the apex of the fixture, and which becomes relatively rougher, and more attractive to bone growth towards the coronal aspect of that part of the fixture which is intended to contact the bony cortex of the intended site.
15. A range or system of components intended for Osseo distraction, or for orthodontic movement of teeth, provided with fittings to facilitate the connection of arch wires, or the cementation of orthodontic components, intended to be used in conjunction with a fixture having an externally threaded intra oral part, or a threaded and flattened intra oral part, substantially as described in this description and the accompanying figures,

1/3

Fig. 1





Fig. 2



2/3

Fig. 3





Fig. 4



10/506632

WO 03/073955

PCT/IB03/00822

3/3

Fig. 5



Fig. 6

Fig. 7





Fig. 8



INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 03/00822

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61C 7/00, A61B 17/66

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61C, A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 10033918 A1 (WALLERIUS, TORSTEN N. DR.), 7 February 2002 (07.02.02), column 2, line 30 - line 41, figures 1-3, claims 1-3, abstract	1-4,7,9,13, 14
Y	column 2, line 30 - line 41, figures 1-3, claims 1-3, abstract	5-6
X	DE 19848599 C1 (KIRSCH, AXEL), 2 November 2000 (02.11.00), figure 1, abstract	1,3,7
X	WO 9831296 A1 (NOBEL BIO CARE AB), 23 July 1998 (23.07.98), abstract	2
Y	abstract	6

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

5 June 2003

Date of mailing of the international search report

06-06-2003

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Nils Nordin/EIs

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB03/00822**Box I** Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 10-12 and 15
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
Claims shall not rely on references to the description or the drawings. See PCT Rule 6.2(a)
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Invention I (claims 1, 3-9, 13 and 14) A fixture with threaded parts to which pressure may be applied.
Invention II (claim 2) An one-piece implant for osseodistraction or orthodontic anchorage.

These groups of inventions are not so linked as to form a single general invention concept. There are no technical relationship among those inventions involving one or more of the same or corresponding technical features.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

29/04/03

International application No.

PCT/IB 03/00822

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	10033918	A1	07/02/02	NONE	
DE	19848599	C1	02/11/00	NONE	
WO	9831296	A1	23/07/98	AU 740669 B	08/11/01
				AU 1680797 A	02/09/97
				AU 5786898 A	07/08/98
				EP 0963183 A	15/12/99
				JP 2001508342 T	26/06/01
				SE 512050 C	17/01/00
				SE 9700155 A	22/07/98
				US 6375465 B	23/04/02
WO	0021455	A1	20/04/00	AU 6073799 A	01/05/00
				EP 1119311 A	01/08/01
				JP 2002527138 T	27/08/02
				NZ 511597 A	26/11/02
				US 6126662 A	03/10/00
US	5015186	A	14/05/91	AT 74733 T	15/05/92
				DE 3870142 D	00/00/00
				EP 0313222 A,B	26/04/89
				US 4854872 A,B	08/08/89

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☒ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.